

The intermittent suction unit is a combination of continuous and intermittent vacuum regulators to use in centralized vacuum systems in hospitals.

- It combines the versatility of an intermittent mode for nasogastric drainage and continuous mode for tracheal, pharyngeal or surgical suction.
- It incorporates a **REG-OFF-INT** device that allows the operator to interrupt aspiration without closing the suction control valve.
- In the intermittent mode, this unit employs a pneumatic logic module to alternate between the *On* and *Off* cycles. The unit is quipped with independent controls to regulate the duration of the *On* and *Off* cycles, the vacuum level and suction flow.
- In the continuous mode it enables suction from 0 to total vacuum (*140 mmHg paediatric*).
- Classified as **High Vacuum / High Regulated Flow** and **Low Vacuum / High Regulated Flow (Paediatric)**.
- Pressing **PUSH** button, the accessories, like filters or DISS connectors, are released for their easy replacement, ensuring the safety of both the user and the patient (*see PUSH Accessories Catalogue*).
- They can be supplied in single and double versions and can be mounted with a direct connector either on a rail fast clamp or on a Ø38,0 mm bar flange. They can be supplied by a flexible tube with different European and American standards (*see Connectors and valves Catalogue*).
- The original set includes the regulator, a disposable filter with safety overflow trap, three disposable filters and a metallic connector for flexible hose.



TECHNICAL SPECIFICATIONS

| | | |
|---------------------------------------|--|------------------------|
| Modes: | Continuous and Intermittent | |
| Range: | Adults: 0-300 mmHg | Paediatric: 0-200 mmHg |
| Vacuum range: | 0 -available vacuum in the network (High Vacuum) | |
| | 0 - 140 mm (Paediatric) | |
| Range of intermittent flow: | Adults: 8 lpm | Paediatric: 2,5 lpm |
| Preset intervals: | ON: 16s | OFF: 8 s |
| Range of continuous flow: | Adults: 0-80 lpm | Paediatric: 0-40 lpm |
| Precision of the vacuum gauge: | ± 3% FS | |
| Dimensions: | 147 x 76 x 101 mm | |
| Weight: | 340 g (without connector) | |

| | DIN 13260 | NF S90-116 | BS 5682 |
|--|------------|------------|------------|
| Just Vac CI Analog. + Connector | 11VPIAAEDN | 11VPIAAENF | 11VPIAAEBS |
| Just Vac CI Paed. Analog.+ Connector | 11VPIPAEDN | 11VPIPAENF | 11VPIPAEBS |
| Just Vac CI Analog. to rail - Knob clamp | 13VPIAAEPD | 13VPIAAEPN | 13VPIAAEPB |
| Just Vac CI Paed. Analog. to rail - Knob clamp | 13VPIPAEPD | 13VPIPAEPN | 13VPIPAEPB |
| Just Vac CI Analog. to Ø38,0 mm tube flange | 14VPIAAEPD | 14VPIAAEPN | 14VPIAAEPB |
| Just Vac CI Paed. Analog. to Ø38,0 tube flange | 14VPIPAEPD | 14VPIPAEPN | 14VPIPAEPB |

¹ For other outputs replace **E** (disposable filter) with: **D** (DISS output), **T** (filter with safety overflow trap), **F** (bottle of 0,5 L), **M** (metal nipple) or **O** (free output).

² For other rail mountings replace **P** (knob clamp) with: **G** (pushbutton clamp), **R** (wall plate) or **H** (bearing plate).

³ Please consult our staff about other gas standards.

⁴ For digital models replace **A** with **D**.



C/ Tungsteno 11-15
 Arganda del Rey, 28500, Madrid
 Telf.: +34 91 871 99 50
 www.itcsal.com itcsal@itcsal.com